

PRODUCT INFORMATION					
PRODUCT DESCRIPTION	15mm Oak Engineered Multi-ply Flooring				
THICKNESS	15mm	WEAR-LAYER	4mm Oak	SURFACE	Golden
WIDTH	125mm	BASE-PLY	11mm Eucalyptus + Poplar		Brushed
LENGTH	600mm	PACK SIZE	1. 2m2		UV Oiled
WEIGHT/PACK	10.20kg	PALLET SIZE	95 boxes/plt		
JOINT METHOD	T&G	PATTERN	Herringbone		
GRADE	Select	WARRANTY	25 Years		

TECHNICAL INFORMATION		
TEST ITEM	TESTING METHOD	TESTING RESULT
Formaldehyde Emission	EN 717-1:2004-10	< LOD (216 h)* (class E1)
Content of PCP	CEN/TR 14823:2004	PCP < 5 x 10 ⁻⁶ n
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK

SPECIFICATION DISCLAIMER

This technical data sheet was written by Wood Flooring Kent and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.