

PRODUCT INFORMATION					
PRODUCT DESCRIPTION	14mm Oak Engineered Multi-ply Flooring				
THICKNESS	14(mm)	WEAR-LAYER	3(mm) Oak	SURFACE	Natural
WIDTH	125(mm)	BASE-PLY	11(mm) Eucalyptus + Poplar		Golden
LENGTH	300-1200(mm)	PACK SIZE	1.8m2		Coffee
WEIGHT/PACK	16.38(kg)	PALLET SIZE	44 boxes/plt		
JOINT METHOD	T&G	PATTERN	Straight Plank		

TECHNICAL INFORMATION		
TEST ITEM	TESTING METHOD	TESTING RESULT
Release of Formaldehyde	BS EN 717-1:2005	E1 (0.2mg/m3)
Slipperiness	CNT/TS 15676:2007(D)	USRV22
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire	BS EN14342:2013	Dfl-s1

SPECIFICATION DISCLAIMER

This technical data sheet was written by Wood Flooring Kent and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.