

| PRODUCT INFORMATION |                                        |             |                          |         |           |
|---------------------|----------------------------------------|-------------|--------------------------|---------|-----------|
| PRODUCT DESCRIPTION | 14mm Oak Engineered Multi-ply Flooring |             |                          |         |           |
| THICKNESS           | 14mm                                   | WEAR-LAYER  | 3mm Oak                  | SURFACE | Natural   |
| WIDTH               | 150mm                                  | BASE-PLY    | 11mm Eucalyptus + Poplar |         | Invisible |
| LENGTH              | 300 - 1200mm                           | PACK SIZE   | 1.44m2                   |         |           |
| WEIGHT/PACK         | 13.1kg                                 | PALLET SIZE | 48 boxes/plt             |         |           |
| JOINT METHOD        | T&G                                    | PATTERN     | Straight Plank           |         |           |

| TECHNICAL INFORMATION   |                              |                |
|-------------------------|------------------------------|----------------|
| TEST ITEM               | TESTING METHOD               | TESTING RESULT |
| Release of Formaldehyde | BS EN 717-1:2005             | E1 (0.2mg/m3)  |
| Slipperiness            | CNT/TS 15676:2007(D)         | USRV22         |
| Thermal Conductivity    | BS EN ISO 10456:2007/AC:2009 | 0.16W/mK       |
| Reaction to Fire        | BS EN14342:2013              | Dfl-s1         |

SPECIFICATION DISCLAIMER

This technical data sheet was written by Wood Flooring Kent and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.